

## 灯具电容器 Capacitors for lamps

型号 Type	特征 Description	安全认证 Safety Approvals	规格 Rating	页码 Page
C62 (CBB60L)	金属化, 塑壳/铝壳封装 Metallized, Plastic or Aluminum case	CQC TUV(Rheinland)	250Vac(50/60Hz): 2.0 $\mu$ F ~ 50.0 $\mu$ F	195
C63 (CBB60H)	金属化, 塑壳封装 Metallized, Plastic case	CQC(250Vac), UL-CUL(construction only)	200Vac(50/60Hz): 5.0 $\mu$ F ~ 75.0 $\mu$ F 240Vac(50/60Hz): 5.0 $\mu$ F ~ 75.0 $\mu$ F 280Vac(50/60Hz): 5.0 $\mu$ F ~ 72.0 $\mu$ F 300Vac(50/60Hz): 5.0 $\mu$ F ~ 55.0 $\mu$ F 330Vac(50/60Hz): 5.0 $\mu$ F ~ 50.0 $\mu$ F 400Vac(50/60Hz): 5.0 $\mu$ F ~ 32.0 $\mu$ F	198
C64 (CBB60M)	金属化, 塑壳封装 Metallized, Plastic case	UL-CUL(construction only)	240Vac(50/60Hz): 5.0 $\mu$ F ~ 75.0 $\mu$ F 280Vac(50/60Hz): 5.0 $\mu$ F ~ 75.0 $\mu$ F 330Vac(50/60Hz): 5.0 $\mu$ F ~ 72.0 $\mu$ F 350Vac(50/60Hz): 5.0 $\mu$ F ~ 55.0 $\mu$ F 400Vac(50/60Hz): 5.0 $\mu$ F ~ 50.0 $\mu$ F	202
C6B	金属化, 铝壳封装 Metallized, Aluminum case	CQC(540Vac), UL-CUL(max. 540Vac)	280Vac(50/60Hz): 4.0 $\mu$ F ~ 100.0 $\mu$ F 330Vac(50/60Hz): 4.0 $\mu$ F ~ 83.0 $\mu$ F 400Vac(50/60Hz): 4.0 $\mu$ F ~ 68.0 $\mu$ F 480Vac(50/60Hz): 4.0 $\mu$ F ~ 60.0 $\mu$ F 540Vac(50/60Hz): 4.0 $\mu$ F ~ 51.0 $\mu$ F 600Vac(50/60Hz): 4.0 $\mu$ F ~ 40.0 $\mu$ F	206
C6C	金属化, 铝壳封装 Metallized, Aluminum case	UL-CUL(max. 620Vac)	280Vac(50/60Hz): 4.0 $\mu$ F ~ 75.0 $\mu$ F 330Vac(50/60Hz): 4.0 $\mu$ F ~ 75.0 $\mu$ F 400Vac(50/60Hz): 3.0 $\mu$ F ~ 68.0 $\mu$ F 480Vac(50/60Hz): 2.0 $\mu$ F ~ 50.0 $\mu$ F 540Vac(50/60Hz): 2.0 $\mu$ F ~ 40.0 $\mu$ F 580Vac(50/60Hz): 1.0 $\mu$ F ~ 34.0 $\mu$ F	211